

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 1 338 326 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
27.08.2003 Bulletin 2003/35

(51) Int Cl.7: B01D 53/94, B01D 53/86

(21) Application number: 03002111.7

(22) Date of filing: 30.01.2003

(84) Designated Contracting States:

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
HU IE IT LI LU MC NL PT SE SI SK TR

Designated Extension States:

AL LT LV MK RO

(30) Priority: 26.02.2002 JP 2002050240

(71) Applicant: Nippon Shokubai Co., Ltd.
Osaka-shi, Osaka 541-0043 (JP)

(72) Inventors:

- Morita, Atsushi
Kakogawa-shi, Hyogo 675-0123 (JP)

- Okamura, Junji
Himeji-shi, Hyogo 672-8043 (JP)
- Masaki, Shinyuki
Himeji-shi, Hyogo 670-0952 (JP)
- Sugishima, Noboru
Himeji-shi, Hyogo 670-0021 (JP)
- Kobayashi, Motonobu
Himeji-shi, Hyogo 671-1241 (JP)

(74) Representative: Henkel, Feller, Hänzeli
Möhlstrasse 37
81675 München (DE)

(54) Process for purification of exhaust gases and catalyst used in the process

(57) The present invention has an object to more enhance the efficiency of the purification of the CO-containing exhaust gases with a catalytic-component-supporting type catalyst, particularly, to enable both achievement of high purification efficiency and long-term stable maintenance of high purification efficiency without increasing the quantity of the catalytic component as supported. As a means of achieving this object, a process for purification of exhaust gases, according to the present invention, is a process for purification of

exhaust gases to remove CO therefrom, and is characterized by comprising the step of bringing the exhaust gases into contact with a catalyst layer at a temperature of 250 to 600 °C, a pressure drop of not more than 100 mmH₂O, and a linear velocity of 0.5 to 10 m/s, wherein the catalyst layer includes a honeycomb-structural catalyst having an opening size of 1.0 to 3.0 mm, an opening ratio of 80 to 80 %, and an inner wall thickness of less than 2 mm.

338 326 A1